

PDU Technology Specification

Date: 24/03/2025

NO:

Customer		DKURVE	
Product Name	Designated Power Distribution Unit for Cabinet		Customer's code
Part Number	SY-PDU19-1U12C13S1.5S2MPC20AB		Picture code
No.	Item	Detailed Description	
1	Product Series	1U Horizontal PDU	
2	Socket Type	IEC C13 socket	
3	Socket Quantity	12	
4	Power Input	Left input	
5	Bracket Install	Horizontal install	
6	Cable with plug	IEC C20 plug	
7	Control Function	On/off switch	
8	Protection Function	No protecting function	
9	Case	Black	
10	Cable Specification	3G 1.5mm ² 2 meters	
11	Product Size	L×W×H=483×44.8×45mm	
12	Mounting Length	461mm	
13	Case Length	433mm	
14	Fittings	Two φ6×16mm cross bolt, two M6 fluctuation nut, PDU instruction handbook (choice)	
15	Product Label	Product Name	Designated Power Distribution Unit for Cabinet
		Specification Model	SY-PDU19-1U12C13S1.5S2MPC20AB
		Rating voltage	250VAC 50/60Hz
		Rating Current	16A
		Max. Current	
		Max. Power	4000W
		Safety	
		Authentication	
		Logo	
		Producer	
No.	Add-In		
1	Socket assemble	NO	
2	Interior Connection Wire	3G1.5mm ²	
3	Interior Connection Style	Standard connection	
4	Fix the Cable	Cable clamp	
5	Module Assemble (From left to right)	Pls refer to the picture	
6	Others		
Made by: Jack		Customer confirm:	Check: Eric
Authorize: Mark			

This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic
gist for arranging production.



IEC C20 Plug (16A)

DIMENSION AND TOLERANCES		
(Unit: mm)		
Length: 483	Mounting length: 461	Product name: Designated Power Distribution Unit for Cabinet
Width: 44.8	Case length: 433	Part no.: SY-PDU19-1U12C13S1.5S2MPC20AB
Height: 45	Case tolerance: ± 3.0	