

PDU Technology Specification

Date: 05/06/2023

NO:

| | | | |
|----------------------|--|--|--|
| Customer | | DKURVE | |
| Product Name | | Designated Power Distribution Unit for Cabinet | Customer's code |
| Part Number | | SY-PDU19-1U6C13S1.5S2MPUKAB | Picture code |
| No. | Item | Detailed Description | |
| 1 | Product Series | 1U Horizontal PDU | |
| 2 | Socket Type | IEC320 C13 socket | |
| 3 | Output Unit | BS1363 | |
| 4 | Power Input | IEC320 C13 socket | |
| 5 | Bracket Install | Horizontal install | |
| 6 | Cable with plug | 3G 1.5mm ² 2 meters cable with 13A UK plug | |
| 7 | Control Function | On/off switch | |
| 8 | Protection Function | | |
| 9 | Shell Color | Black | |
| 10 | Cable Specification | 3G 1.5mm ² 2 meters | |
| 11 | Product Size | L×W×H=482.6×45×45mm | |
| 12 | Mounting Length | 461.6mm | |
| 13 | Case Length | 431mm | |
| 14 | Fittings | Two φ6×16mm cross bolt 、 two M6 fluctuation nut、 PDU instruction handbook (choice) | |
| 15 | Product Label | Product Name | Designated Power Distribution Unit for Cabinet |
| | | Specification Model | SY-PDU19-1U6C13S1.5S2MPUKAB |
| | | Rating voltage | 250VAC 50/60Hz |
| | | Rating Current | 10A |
| | | Max. Current | 10A |
| | | Max. Power | 2500W |
| | | Safety Authentication | |
| | | Logo | |
| | | Producer | |
| No. | Add-In | | |
| 1 | Socket assemble | IEC320 C13 | |
| 2 | Interior Connection Wire | Copper Bar | |
| 3 | Interior Connection Style | | |
| 4 | Fix the Cable | Screw fix without spot | |
| 5 | Module Assemble (From left to right) | On/off switch, IEC320 C13 | |
| 6 | Others | | |
| Made by: Jack | | Customer confirm: | Check: Eric Authorize: Mark |

This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.